

DAMAS Company. Tel:+962 6 4205448 E-mail: info@decorete.com Website: www.decorete.com

Deco LR 20

Liquid Stamp Release

DESCRIPTION:

Deco LR 20 is a blend of natural and synthetic chemicals that provides quick, easy and clean release of concrete from decorative concrete texturing tools.

USES:

Deco LR 20 is ideal for use on fresh concrete surfaces, particularly where a powder release may cause damage to adjacent surfaces, or where no secondary color is required. Deco LR 20 can be used on polyurethane, metal, fiberglass and rubber decorative concrete tools for the efficient and clean release from the fresh concrete surface.

FEATURES/BENEFITS:

- Ensures safe and efficient release of concrete from decorative concrete tools/Minimizes wear and tear to decorative concrete tools.
- Is a clear liquid and will not affect the final appearance of a concrete project.
- Provides a release option for projects where use of a powder release is not desired

SHELF LIFE:

One year when stored in a cool, dry, well-ventilated area.

PACKAGING:

Deco LR 20 is available in 18 liter plastic containers.

COVERAGE:

Each container covers approximately 90 m²

SURFACE PREPARATION:

Clean existing debris from all stamping tools. Ensure that the concrete is sufficiently set, and that all bleed water has dissipated from the surface to be worked on. The concrete surface should also be at a stage where it is able to support the load of workers, as well as any tools that are required.

APPLICATION:

Liberally apply Deco LR 20 by commercial sprayer to the decorative concrete tools and to the concrete surface. Ensure that the surface is uniformly covered for proper release of the decorative concrete tools. Deco LR 20

should not be applied too far in advance, as evaporation of the product may occur, causing a less than clean release of stamping tools.

NOTE: Deco LR 20 should be applied in a clean, even mist in order to prevent spotting. Place the decorative concrete texturing or stamping mats over the area that has been covered with Deco LR 20 using an impact tool, ensure that the concrete surface is adequately stamped for depth of texture. Remove the decorative concrete texturing mats from the concrete surface. Allow the concrete to set for a minimum of 24 hours.

PRECAUTIONS:

Use Deco LR 20 in an adequately ventilated area. It is recommended that a painter's mask or a personal respirator be worn during the sprayer application. Combustible liquid. Keep away from ignition sources.

HEALTH AND SAFETY:

Avoid contact with skin and eyes. If skin contact occurs, wash affected area immediately with soap and water.

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.

WARRANTY (DISCLAIMER):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase

KEEP OUT OF REACH OF CHILDREN