

DAMAS Company. Tel:+962 6 4205448 E-mail: info@decorete.com Website: www.decorete.com

Deco Stone Grout

Stone Grout

DESCRIPTION:

Ready to use cement based polymer modified mortar specially formulated to be used as stone joint filler.

USES:

Deco Stone Grout is used to fill stone joints whether natural or artificial with colored mortar filler.

ADVANTAGES:

- Reduces water absorption through joints.
- Available in more than 40 standard colors
- Factory controlled blending for consistent results on the job
- Convenience of handling and transporting one product
- Easy handling on difficult access and multi-story jobs
- Excellent workability

APPLICATION:

Opening joints:

After stone firmly set, joints between stone blocks must be opened with an electrical grinder to about 1/2" in depth and minimum 1/2" in width, then joint should be thoroughly cleaned from any dust or loose material.

Mixing:

Empty Deco Stone Grout bag into a suitable mixing container adding about 4-5 liters of potable water, using a forced action mixer or by a heavy duty drill for at least 2 minutes until mixture homogeneity is acquired.

Application:

Using thin specula force Deco Stone Grout slightly into cleaned joints until excessive materials eject out of joints, make sure that all gaps and skips are filled completely, and let the materials to set for about 30 minutes.

Finishing:

Clean any surplus and excessive grout with a dry whisk broom after it get crumbly, sweep it slightly to obtain the required grouting shape and surface. Using a fine brush polish the grout surface to remove any existed roughness.

PACKAGING:

15 kg plastic bags.

COVERAGE:

Refer to grout consumption chart.

SHELFLIFE:

Six months if protected from the weather Bags of Deco Stone Grout must be stored in a dry area, preferably off the floor.

TECHICAL DATA:

Density	1720 kg/m3
Compressive strength	ASTM C109-90
Bond strength	(BS EN 1542:1999)
Frost Resistance	Excellent
Non-combustible	CAN4-ULC-S114-M80 Rated non-combustible

HEALTH AND SAFETY:

Deco Stone Grout dust is an irritant, and paper dust protection masks should be worn while it is being mixed. The wet mixture is alkaline, and prolonged skin contact should be avoided

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.

WARRANTY (DISCLAIMER):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase.

KEEP OUT OF REACH OF CHILDREN