

Deco Plaster 202

Splatter Dash Coat

DESCRIPTION:

Ready to use cement based polymer modified mortar specially formulated to be used as a splatter dash coat prior to the application of Brown coat.

USES:

Deco plaster 202 is used as a key coat for enhanced key action between, concrete, brick, and masonry substrate and plaster coat.

ADVANTAGES:

- Factory controlled blending for consistent results on the job
- Convenience of handling and transporting one product
- Easy handling on difficult access and multi-story jobs
- Excellent workability
- Excellent bonding to walls and ceilings even over fair face concrete

APPLICATION:

Substrate:

All surfaces should be sound, and free from contamination such as oil, grease, or any other compounds that might inherit adhesion

Mixing:

Mix each 50 kg bag of Deco plaster 201 with 9-10 liters of clean water, preferably using an electric mixer.

Application:

Deco plaster 201 can be applied by Tyrolean box or using spray machine onto wetted prepared surface. Insure full coverage for better adhesion and unified absorption of successive plaster layers

Curing:

Proper curing is important especially in hot or windy conditions. Provide sufficient moisture to permit continuous hydration of the cementitious materials Protect from extreme weather, cure with water for 3day

PACKING:

- 50kg plastic bags.
- 30 Kg plastic bags.

COVERAGE:

Each 50 kg bag yields around 8-10 m²

STORAGE:

Six months if protected from the weather
Bags of Deco plaster 202 must be stored in a dry area, preferably off the floor on a timber pallet.
Rotate the stock to ensure that the oldest material is used first.

TECHNICAL DATA:

| | |
|-----------------------------|--|
| Bulk Density | 1.8± 0.1 MPa |
| Wet Density | 2.1 ± 0.1 MPa |
| Max particle size | 4 mm |
| Compressive strength | 20 Mpa @ 28 days |
| Bond strength | 1.3 Mpa@ 28 days |
| Frost Resistance | Excellent |
| Non-combustible | CAN4-ULC-S114-M80 Rated non-combustible |

HEALTH AND SAFETY:

Deco plaster 202 plaster dust is an irritant, and paper dust protection masks should be worn while it is being mixed. The wet plaster is alkaline, and prolonged skin contact should be avoided.

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.

WARRANTY (DISCLAIMER):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase

KEEP OUT OF REACH OF CHILDREN