

Deco seal

Clear Acrylic Sealer

DESCRIPTION:

Decoseal Clear Sealer is a 100% acrylic solvent base concrete sealer and curing agent. It has been specifically formulated for sealing and protecting plain and colored concrete, masonry, precast concrete, terrazo tiles and cementitious overlayments.

Recommended for use over Stamped Concrete, Decorete® Overlay, acid stained floors and any other concrete or masonry surface where a clear bright finish is desired.

Decoseal clear sealer is a non-styrenated acrylic sealer, non-yellowing and resistant to oil, gasoline, grease, acid, deicing salts, ultra violet rays, wet and dry abrasion, and most household chemicals.

Decoseal enhances the color of stamped concrete, overlays and acid stained floors, and it adds life to your decorative concrete surface while creating a hard and long lasting protective shield over the concrete surface

Decoseal is a ready to use product. Do not thin. Use straight from the pail.

ADVANTAGES:

- Anti-dust
- Non-yellowing.
- Enhances color of decorative concrete.
- Reduces alkali/efflorescence attack.
- Resistant to mild chemicals.
- Prolongs life of surface.
- Freeze thaw resistance
- Maintains surface cleanliness.
- Improves weathering resistance of natural and manufactured brick products.

SURFACE PREPARATION:

Surface must be sound, dry and free of oil, grease, curing compounds and any other foreign material that may inhibit the penetration of the sealer into the surface.

STAMPED CONCRETE:

Stamped concrete should be washed as soon as possible to remove the release powder, dirt or other contaminants. The surface must be completely dry before applying Decoseal; surface moisture may cause delamination, whitening, cloudiness and unappealing results.

APPLICATION:

Decoseal clear sealer can be applied by paint roller (1/2" to 3/4" nap), or sprayer. Apply two or more thin coats. Allow to dry tack free between coats.

Dry time is approximately 2 hours at 21° C, but varies depending on temperature, wind and humidity. Protect the application from rain for 24 hours. Allow 24 hours at 21 °C before opening area to traffic.

COVERAGE:

18 liter pail will yield approximately 60 m² per two coats

TECHNICAL DATA:

Color	Water clear
Solids	Deco Seal 100 : ≥ 20 % Deco Seal 200 : ≥ 25 % Deco Seal 300 : ≥ 30 %
Water Absorption	25 % improve
Coverage Rate	5 m ² / liter/ coat
Recoat time	2 to 4 hours

PACKAGING

Decoseal is readily available in 5 liter and 18 liters pails. Also available in (200 liters) drums.

STORAGE:

Store under cool, dry conditions away from direct sunlight. Properly stored Decoseal has a useable lifetime of approximately one (1) year.

Deco seal

Clear Acrylic Sealer

PRECAUTIONS:

COMBUSTIBLE: Contains flammable materials, Vapor and spray mist maybe harmful. Overexposure may cause lung damage and allergic skin and respiratory reactions. Repeated and prolonged exposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness, and loss of coordination are signs that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.

WARRANTY (DISCLAIMER):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase

KEEP OUT OF REACH OF CHILDREN