

Deco Top 200

Dry Shake Floor Hardener

DESCRIPTION:

DecoTop200 is a ready to use non-metallic dry shake Hardener.

DecoTop200 is formulated to easily integrate into the surface offers freshly placed concrete.

DecoTop200 densifies the surface of the slab, increases its resistance to wear, freeze and thaw cycles, heavy traffic and enhances light reflecting while greatly improving its appearance.

USES:

DecoTop200 is used in institutional, industrial, commercial and residential applications for interior flat concrete floors where a workhorse, high wears and abrasion resistance is desired.

COMPOSITION:

DecoTop200 is formulated with specially graded silica quartz aggregates, top quality Portland cement, and proprietary additives.

PACKAGING:

Deco Top200 is packaged in 30Kg bags.

COVERAGE:

Each bag covers between 10 and 15 square meters for normal applications.

SHELF LIFE:

6 months when stored properly in a dry/moisture free environment.

APPLICATIONS:

After initial floating and all excess bleed water has dispersed, first application of Deco Top 200 hardener may be applied.

Broadcast first application using about 60% of recommended amount and let it remain

on the surface for several minute or until the DecoTop200 hardener has wetted out sufficiently, then float with a wood or magnesium float. Immediately broadcast the second application with remaining of Deco Top 200 hardener and let it wet out for several minutes then trowel with steel trowel, if needed in some areas may have to be touched up with more material.

CAUTION: Do not over trowel. Do not sprinkle or fog water on concrete. This will cause variation on color intensity.

TECHICAL DATA:

Powder Dry Density	1700Kg/m ³
Wet Density	1800Kg/m ³
Compressive Strength	BS6319:pt.2:1983
Non-combustible	CAN4-ULC-S114-M80 Rated on-combustible

HEALTH AND SAFETY:

Use face mask or respirator. Do not allow getting into eyes. Keep out of the reach of children. Prolonged breathing will cause throat and lung irritation. Protect all adjacent areas.

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.

WARRANTY (DISCLAIMER):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase.

KEEP OUT OF REACH OF CHILDREN