

DAMAS Company. Tel:+962 6 4205448 E-mail: info@decorete.com Website: www.decorete.com

Deco Finish

Cement base putty

DESCRIPTION:

Deco Finish is a white cement based fine powder which provides an ideal base for concrete / cement plastered walls and ceilings.

Deco Finish provides a smooth finish for further application of all kinds of paints. Its water repelling properties prevents flaking of your expensive paints

Deco Finish proves very effective when working under severe time constraints as it can be used even before the cement plaster is completely dry. It is ideal Finish for bathroom, balcony walls, and exterior applications where wet conditions are available.

USES:

Deco Finish is used for rendering and leveling fine plaster before the application of paints.

Deco Finish is also used in filling cracks and holes in walls and ceilings prior to painting

Deco Finish has a variety of applications and can be used on concrete, rendered walls, hollow blocks, pre-cast walls, concrete ceilings, calcium silicate bricks, aerated light-weight blocks etc.

ADVANTAGES:

- Water-resistant hence it doesn't peel-off due to dampness or minor seepages in the wall surface.
- It remains strongly adhered to the plastered/concrete wall surface and provides a durable base to the top-coat of expensive paint.
- Brings-out the true tone and shade of expensive paint applied over it.
- Provides Protection and enhances the beauty of your expensive paints
- Gives smooth finish and does not require primer coat before application of paint
- Excellent adhesion strength

APPLICATION:

Surface Preparation: Clean the surface to remove loose particles, dirt, grease etc. Cracks and holes should be filled and leveled. Soak the surface with clean water.

MIXING:

Mix one bag of Deco Finish with 6 lt. water to make a smooth homogeneous paste. Allow the mix to stand for 10 minutes, stir well and use the paste within 2 hours.

APPLICATION TECHNIQUE

Apply Deco Finish using a painter's Finish knife, in layers up to 1 mm thickness. Allow to dry overnight, before applying the 2nd coat. After drying, polish the surface with fine sand paper, and wipe off any residual dust. Cure with water for more strength if required.

PACKAGING:

20 Kg plastic bags

COVERAGE:

14-15 m² per bag@ 1 mm thickness wet film

SHELF LIFE:

Unopened bags can be stored for up to 12 months in a cool, dry and weatherproof environment. Bags must be stored off the floor

Curing:

Curing is not required after applications of Deco Finish, However, after application, just sprinkling of water over applied surface for 2 days will enhance the hydration of cement particles which will give better results.

LIMITATIONS:

Do not install over control or expansion joints.

TECHNICAL DATA:

Fresh wet density	1.8 ± 0.1
Pot Life	2 hours@ 25 °C
Setting Time	Initial Set 1 to 3 hours Final set 3 to 8 hours
Compressive Strength	28 days 14Mpa
Adhesion strength	28 days 2.38 Mpa



DAMAS Company. Tel:+962 6 4205448 E-mail: info@decorete.com Website: www.decorete.com

Deco Finish

Cement base putty

HEALTH & SAFETY:

This product is non-toxic but contains cement. Use good occupational health and safety practices to avoid personal contact. Decorete recommend the use of dust masks, eye protection and wearing of gloves when handling this product

SERVICES:

For further information on this product together with advice on application, please contact The Technical Advisory Department

WARRANTY (DISCLAIMER):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase

KEEP OUT OF REACH OF CHILDREN.