

Deco Guard WB

Water base Penetrating Water repellent

DESCRIPTION:

Deco Guard WB is a water base water repellent mixture of silane and siloxane.

Deco Guard WB serves as high quality, general-purpose water repellents for impregnating and priming mineral surfaces

Deco Guard WB reduces the capillary absorption, but does not clog pores or capillaries. There is therefore little or no impairment of the building material's ability to "breathe".

USES:

Deco Guard WB is excellent water repellent for many absorbent mineral substrates, such as:

- Natural and artificial stone
- Brick
- Cement fiberboards
- Plasters and renders
- Fibrous cement

Deco Guard WB is not suitable for less absorbent, dense natural stone, especially limestone, marble and reinforced concrete for bridges and roads

ADVANTAGES:

- Environment friendly
- Good depth of penetration.
- High alkaline resistance.
- Effective even on damp substrates
- Allows substrate to breath
- Provides good adhesion for paints
- Reduces efflorescence, scaling and spalling

APPLICATION:

Flooding, preferably not under pressure is the best technique for applying Deco Guard WB, apply several coats, wet on wet, until the substrate is saturated. Generally at least two applications suffice for all substrates.

Best results are obtained by applying Deco Guard WB on clean and dry substrates. As a standard procedure, fresh concrete should be allowed to dry for 28 days before application. All repointing must be completed and allowed to cure at least 3 days. Concrete repair and replacement must be completed prior to application.

Before applying Deco Guard WB be sure to cover windows and other non-absorbent surfaces properly because the product cures so quickly that it will be extremely difficult. If not impossible to remove .wipe off any splashes on window panes immediately, using a solvent if necessary.

PACKAGING:

Deco Guard WB is available in 18 liter plastic containers.

STORAGE:

Deco Guard WB has a shelf life of at least 12 months from date of manufacture when stored between 0°C and 35°C in the tightly closed original container, the container must be protected against sunlight.

COVERAGE:

The Consumption and the effectiveness of Deco Guard WB vary according to type of substrate and should only be determined on site by testing a small area of the material to be treated.

TECHNICAL DATA:

Appearance	Milky, White
Active content	approx. 25 wt. %
Density at 25 °C, approx	[g/cm ³] 0.95
Viscosity, dynamic at 25 °C	approx. 12 mPa.s

HEALTH AND SAFETY:

Deco Guard WB is non-flammable. Deco Guard WB should be kept closed when not in use and should be stored at temperatures below 40° C.

Avoid contact with skin and eyes. If skin contact occurs, wash affected area immediately with soap and water.

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.



DAMAS Company.
Tel : +962 6 4205448

E-mail : info@decorete.com
Website : www.decorete.com

Deco Guard WB

Water base Penetrating Water repellent

WARRANTY (Disclaimer):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase

KEEP OUT OF REACH OF CHILDREN.