

Deco Guard AR

Curing/Sealing compound

DESCRIPTION:

Deco Guard AR is water based acrylic compound designed to cure fresh colored plaster and provide a protection against weathering conditions.

Deco Guard AR reduces water absorption by 80% as opposed to untreated surfaces, and improves stain resistance.

Deco Guard AR binds sand and cement particles to form a tough, flexible yet breathable film.

Deco Guard AR strengthens mortar joints, reduces efflorescence on brick and acts as a color rejuvenator on older painted or colored surfaces

USES:

Deco Guard AR can be used for the following applications:

- Top coat for all Decorete® Architectural Coatings
- Sealer for masonry and concrete substrates.
- Interior and exterior application.
- All locations where a clear weather shield is desired

ADVATAGES:

- Cures fresh stucco without the need for water
- Reduce water absorption significantly.
- Protects from carbonation
- Resists mildew and fungus growth
- Outstanding color retention
- Highly durable
- Breathable
- Excellent resistance to dirt pick up.
- Excellent freeze/thaw stability and general excellent Weather ability

CAUTIONS & LIMITATIONS:

- Do not apply when ambient, surface and material temperatures are less than 5°C during application and curing period
- Protect applied product from moisture, standing water and inclement weather until fully dry.
- Not recommended for floor applications
- DO NOT use for basement of underground masonry. Under hydrostatic pressure, water might penetrate treated surface.

TECHNICAL DATA

Recoat	wet on dry
Appearance	Milky white
Viscosity	130 cps
Ph level	6.7
Effloresces resistance	Moderate

COVERAGE

Deco Guard AR can be diluted at a rate of 1:2 with water, which corresponds to coverage of 150 m².

Note: Coverage rates are theoretical and for estimations purpose only, it is advised to conduct a field test to determine coverage rates and number of coats required.

APPLICATION:

Surfaces to be treated must be dry, clean and sound, free of all ice, snow, dew and frost and all dust, dirt, oil, grease and other deleterious materials detrimental to a positive bond.

Cracks, loose mortar and spalling surfaces must be repaired prior to applying Deco Guar AR.

Thoroughly stir Deco Guard AR before each use. Apply Deco Guard AR by roller, brush or low pressure sprayer. Avoid applying too much sealer in any one coat. Avoid dripping or streaking resulting from excessive application in any one area.

Allow first coat to dry for approximately 2 hours, then apply a second thin coat following instructions in step one.

PACKAGING:

Deco Guard AR is readily available in 5 liter and 18 liters pails.

HEALTH AND SAFETY

Deco Guard AR is non-flammable, nontoxic under normal conditions of use. Harmful if taken internally.

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection



DAMAS Company.
Tel :+962 6 4205448

E-mail : info@decorete.com
Website : www.decorete.com

Deco Guard AR

Curing/Sealing compound

SERVICES:

For further information on this product together with advice on application, please contact the Technical Advisory Department.

WARRANTY (Disclaimer):

Decorete® fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Decorete®'s responsibility shall not exceed either the refund of the purchase

KEEP OUT OF REACH OF CHILDREN